

Huon Series - 160

[AES-12-ET-DIL1600615B]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 18W
Efficacy	80lm/W
Correlated Colour Index (CRI)	>80, TBC
IP Rating	67, TBC
IK Rating	09
Voltage	AC220-240V
Size - Diameter	Diameter: 160mmØ
Size - Height	Height: 170mmH
Beam Angle	TBC, Beam Angle: 5°, Beam Angle: 8°, Beam Angle: 10°, Beam Angle: 12°, Beam Angle: 20°, Beam Angle: 25°, Beam Angle: 30°, Beam Angle: 40°, Beam Angle: 45°, Beam Angle: 60°, Beam Angle: 15° x 55°, Beam Angle: 20° x 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2200K, CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K, CCT: 6500K, CCT: RGB, CCT: RGBW
Accessories	DMX Controls
Lens Options	TBC, PMMA + Anti-UV Lens
Material of Housing	Housing Material: Stainless Steel and Aluminum
Operating Temperature	Operating Temperature: -20°C to +45°C

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 160mmØ
Size - Height	Height: 170mmH
Beam Angle	TBC, Beam Angle: 5°, Beam Angle: 8°, Beam Angle: 10°, Beam Angle: 12°, Beam Angle: 20°, Beam Angle: 25°, Beam Angle: 30°, Beam Angle: 40°, Beam Angle: 45°, Beam Angle: 60°, Beam Angle: 15° x 55°, Beam Angle: 20° x 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Accessories	DMX Controls

ATTRIBUTE	VALUES
Material of Housing	Housing Material: Stainless Steel and Aluminum
Operating Temperature	Operating Temperature: -20°C to +45°C

Certification and Compliance

