

# Kalvara Series - 100



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	10W, 12W
Efficacy	105lm/W
Correlated Colour Index (CRI)	>80, >90, TBC
MacAdam Ellipse (SDCM)	<5
IP Rating	20
Voltage	AC220-240V
Light Source & Brand	LED: COB
Driver	Driver: Built In
Size - Diameter	Diameter: 100mmØ
Size - Height	Height: 131mmH
Cut Out Size - Diameter	Cut Out: 85mmØ
Weight	Weight: 0.58kg
Beam Angle	TBC, Beam Angle: 24°, Beam Angle: 30°, Beam Angle: 45°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, DALI Dimmable

ATTRIBUTE	VALUES
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Optics Material: Aluminium & Transparent Tempered Glass
Operating Temperature	Operating Temperature: -20°C to +40°C
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Reflector / Internal Colour	Reflector/Internal: White, Reflector/Internal: Black, Reflector/Internal: Gold
Correlated Colour Temperature (CCT)	CCT: 3CCT: 2700K+3500K+5000K, CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K
Mounting Options	Recessed
Lifetime	Reported L80 @ 85° >55,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

## Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 100mmØ
Size - Height	Height: 131mmH
Beam Angle	TBC, Beam Angle: 24°, Beam Angle: 30°, Beam Angle: 45°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

## Certification and Compliance

