

# Ulara Series - 190

[AES-27-DL440-190]



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 18W, 25W, 35W
Efficacy	90-100lm/W
Correlated Colour Index (CRI)	>90
MacAdam Ellipse (SDCM)	<5
IP Rating	44
Voltage	AC220-240V, 50/60Hz
Light Source & Brand	LED: Bridgelux COB
Size - Diameter	Diameter: 190mmØ
Size - Height	Height: 149mmH
Cut Out Size - Diameter	Cut Out: 170mmØ
Weight	Weight: 1.9kg

ATTRIBUTE	VALUES
Beam Angle	TBC, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Optics Material: Polycarbonate
Operating Temperature	Operating Temperature: -20°C to 45°C
Trim / Outer Colour	TBC, Trim/Outer: White
Reflector / Internal Colour	TBC, Reflector/Internal: Silver
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 3CCT: 3000K+4000K+5000K
Mounting Options	Recessed
Lifetime	Reported L80 @ 85° >55,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

## Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 190mmØ
Size - Height	Height: 149mmH
Beam Angle	TBC, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to 45°C

## Certification and Compliance

