

Profile - LE2409

[AES-06-LE2409]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	3.3W, 6W, TBC
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 6000K
Lumens	100lm/W @2700K, 104lm/W @3000K, 108lm/W @4000K, 104lm/W @6000K
Product Code	D6140-24V-4mm
Cutting Unit	50mm
Correlated Colour Index (CRI)	>90
MacAdam Ellipse (SDCM)	<2

ATTRIBUTE	VALUES
Light Source & Brand	LED: SMD
IP Rating	20, 65, TBC
Voltage	DC 24V
LED's p/m	200
Size - Width	Width: 23.8mmW
Size - Height	Height: 8.8mmH
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Silver
Mounting Options	Recessed
Beam Angle	Beam Angle: 110°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Operating Temperature	Operating Temperature: -25°C to 40°C
Lifetime	Reported L80 @ 85° >60,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

Product Options

ATTRIBUTE	VALUES
Size - Height	Height: 8.8mmH
Beam Angle	Beam Angle: 110°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Operating Temperature	Operating Temperature: -25°C to 40°C

Certification and Compliance

