

Norwell Series - 145

[AES-27-DL412A-145]



Technical Specifications

| ATTRIBUTE | VALUES |
|-----------------------------------|--------------------------------------------------|
| Wattages | 10W, 13W |
| Efficacy | 100-110lm/W |
| Correlated Colour Index (CRI) | >90 |
| MacAdam Ellipse (SDCM) | <4 |
| IP Rating | 54 |
| Voltage | AC220-240V, 50/60Hz |
| Light Source & Brand | LED: SMD 2835 |
| Size - Diameter | Diameter: 145mmØ |
| Size - Height | Height: 79mmH |
| Cut Out Size - Diameter | Cut Out: 120mmØ |
| Weight | Weight: 0.3kg |
| Beam Angle | Beam Angle: 60° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, DALI Dimmable |
| Material of Housing | Housing Material: Aluminium |
| Material of Optics- Glare control | Optics Material: Polycarbonate |

| ATTRIBUTE | VALUES |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Operating Temperature | Operating Temperature: -20°C to 45°C |
| Trim / Outer Colour | Trim/Outer: White, Trim/Outer: Black |
| Reflector / Internal Colour | Reflector/Internal: Silver |
| Correlated Colour Temperature (CCT) | CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K |
| Mounting Options | Recessed |
| Lifetime | Reported L80 @ 85° >55,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes |

Product Options

| ATTRIBUTE | VALUES |
|-----------------------|--------------------------------------------------|
| Size - Diameter | Diameter: 145mmØ |
| Size - Height | Height: 79mmH |
| Beam Angle | Beam Angle: 60° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, DALI Dimmable |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -20°C to 45°C |

Certification and Compliance

