

Norwell Series - 170

[AES-27-DL412A-170]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	15W, 18W
Efficacy	100-110lm/W
Correlated Colour Index (CRI)	>90
MacAdam Ellipse (SDCM)	<4
IP Rating	54
Voltage	AC220-240V, 50/60Hz
Light Source & Brand	LED: SMD 2835
Size - Diameter	Diameter: 170mmØ
Size - Height	Height: 94mmH
Cut Out Size - Diameter	Cut Out: 140mmØ
Weight	Weight: 0.32kg
Beam Angle	Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Optics Material: Polycarbonate

ATTRIBUTE	VALUES
Operating Temperature	Operating Temperature: -20°C to 45°C
Trim / Outer Colour	Trim/Outer: White
Reflector / Internal Colour	Reflector/Internal: Silver
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K
Mounting Options	Recessed
Lifetime	Reported L80 @ 85° >55,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 170mmØ
Size - Height	Height: 94mmH
Beam Angle	Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to 45°C

Certification and Compliance

