

Cleanroom 1230

[AES-27-CK22-1230]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 40W, 45W, 48W, 52W, 60W, 72W
Efficacy	120lm/W
Correlated Colour Index (CRI)	>80, >90, TBC
MacAdam Ellipse (SDCM)	<6
IP Rating	65
IK Rating	08
Voltage	AC220-240V, 50/60Hz
Light Source & Brand	LED: SMD 2835
Driver	VSI Flicker Free
Size - Length	1230mmL
Size - Width	Width: 325mmW
Size - Height	Height: 81mmH
Weight	Weight: 8.8kg
Beam Angle	Beam Angle: 90°

ATTRIBUTE	VALUES
Dimming Options	Non-Dimmable, TBC, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Optics Material: PMMA
Corrosion Resistance	Corrosion Resistance: C4
Operating Temperature	Operating Temperature: -30°C to +40°C
Trim / Outer Colour	Trim/Outer: White
Reflector / Internal Colour	Reflector/Internal: Opal
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K
Mounting Options	Plaster Recessed
Lens Options	Frosted PMMA Lens
Lifetime	Reported L80 @ 55° >102,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

Product Options

ATTRIBUTE	VALUES
Size - Length	1230mmL
Size - Height	Height: 81mmH
Beam Angle	Beam Angle: 90°
Dimming Options	Non-Dimmable, TBC, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -30°C to +40°C

Certification and Compliance

