

Tube Series - 126

[AES-27-HLS30R03-4W]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	4W
Efficacy	80lm/W
Correlated Colour Index (CRI)	>85, >90, TBC

ATTRIBUTE	VALUES
MacAdam Ellipse (SDCM)	<5, <3
IP Rating	67, TBC
IK Rating	09
Voltage	AC220-240V
Light Source & Brand	LED: Osram SMD, LED: CREE SMD
Size - Length	Length: 124mmL
Size - Width	Width: 30mmW
Size - Height	Height: 32mmH
Cut Out Size - Length	Cut Out: 124mmL
Cut Out Size - Width	26mmW
Mounting Options	Recessed
Beam Angle	10*110°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 6500K, CCT: RGB, CCT: RGBW
Accessories	DMX Controls
Lens Options	TBC, PMMA + Anti-UV Lens
Material of Housing	Housing Material: Stainless Steel
Operating Temperature	Operating Temperature: -20°C to +40°C
Lifetime	Reported L80 @ 85° >90,700 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 124mmL
Size - Height	Height: 32mmH
Cut Out Size - Length	Cut Out: 124mmL
Cut Out Size - Width	26mmW
Beam Angle	10*110°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Accessories	DMX Controls

ATTRIBUTE	VALUES
Material of Housing	Housing Material: Stainless Steel
Operating Temperature	Operating Temperature: -20°C to +40°C

Certification and Compliance

