

Narooma Series- 600

[AES-04-CR0100-600]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	50W
Efficacy	95lm/W, 100lm/W
Correlated Colour Index (CRI)	>80, >90
MacAdam Ellipse (SDCM)	<3
IP Rating	20
IK Rating	05
Voltage	AC220-240V, 50/60Hz
Light Source & Brand	LED: Lumileds 2835
Driver	Driver: BOKE, Driver: Eaglerise, Driver: SCPOWER
Size - Diameter	Diameter: 600mmØ
Size - Height	Height: 100mmH
Weight	Weight: 5.7kg
Beam Angle	Beam Angle: 120°
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 6000K
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Optics Material: Polycarbonate
Operating Temperature	Operating Temperature: -20°C to 35°C
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable

ATTRIBUTE	VALUES
Mounting Options	Suspended, TBC, Recessed, Ceiling Mounted
Lens Options	TBC, MicroPrismatic Diffuser, Opal Diffuser
Accessories	5m Suspension Kit, 2m Suspension Kit
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 600mmØ
Size - Height	Height: 100mmH
Beam Angle	Beam Angle: 120°
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to 35°C
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Accessories	5m Suspension Kit, 2m Suspension Kit

Certification and Compliance

