

# Eltham Series

[AES-27-DL103]



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	5W, 8W, 10W, 13W

ATTRIBUTE	VALUES
Efficacy	100-110lm/W
Correlated Colour Index (CRI)	>90
MacAdam Ellipse (SDCM)	<5
IP Rating	65
Voltage	AC220-240V, 50/60Hz
Light Source & Brand	LED: SMD 2835
Size - Diameter	Diameter: 80mmØ, Diameter: 90mmØ, Diameter: 110mmØ
Size - Height	Height: 30mmH, Height: 40mmH, Height: 50mmH
Cut Out Size - Diameter	Cut Out: 68mmØ, Cut Out: 75mmØ, Cut Out: 90mmØ
Weight	Weight: 0.2kg, Weight: 0.43kg, Weight: 0.58kg
Beam Angle	Beam Angle: 36°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Optics Material: Polycarbonate
Operating Temperature	Operating Temperature: -20°C to 45°C
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Reflector / Internal Colour	Reflector/Internal: Silver
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 2CCT: 3000+4000K
Mounting Options	Recessed
Lifetime	Reported L80 @ 85° >55,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

## Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 80mmØ, Diameter: 90mmØ, Diameter: 110mmØ
Size - Height	Height: 30mmH, Height: 40mmH, Height: 50mmH
Beam Angle	Beam Angle: 36°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, DALI Dimmable
Material of Housing	Housing Material: Aluminium

ATTRIBUTE	VALUES
Operating Temperature	Operating Temperature: -20°C to 45°C

## Certification and Compliance

