

Waarre Series



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 20W
Efficacy	90lm/W
Correlated Colour Index (CRI)	>80, TBC
IP Rating	65, TBC
IK Rating	10
Voltage	AC220-240V
Light Source & Brand	LED: Epistar SMD
Mounting Options	Surface Mounted, TBC, Wall Mounted, Ceiling Mounted

ATTRIBUTE	VALUES
Beam Angle	TBC, Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 1-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 6000K
Accessories	Microwave Sensor, PIR Sensor, Dimming Sensor (0%-100%-25%-10%-0%), Emergency
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Grey
Material of Housing	Housing Material: Aluminium

Product Options

ATTRIBUTE	VALUES
Beam Angle	TBC, Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 1-10V Dimmable, DALI Dimmable
Accessories	Microwave Sensor, PIR Sensor, Dimming Sensor (0%-100%-25%-10%-0%), Emergency
Material of Housing	Housing Material: Aluminium

Certification and Compliance

