Australian EcoTech Solutions
1/123 Merrindale Drive
Croydon South VIC 3136
Australia

Cabarlah Series - 350

[AES-18-CLR350]



Australian EcoTech Solutions
1/123 Merrindale Drive
Croydon South VIC 3136
Australia

Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 22W, 24W, 26W, 28W, 30W
Efficacy	90lm/W
Correlated Colour Index (CRI)	>80, TBC
IP Rating	65, TBC
IK Rating	10
Voltage	AC100-277V, 50/60Hz
Light Source & Brand	LED: Epistar SMD
Driver	Driver: BOKE
Size - Diameter	Diameter: 350mmØ
Size - Height	Height: 110mmH
Weight	Weight: 2.5kg
Beam Angle	TBC, Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die-Casting Aluminum
Material of Optics- Glare control	Optics Material: Polycarbonate
Operating Temperature	Operating Temperature: -30°C to 60°C
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Grey
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 6000K
Mounting Options	Surface Mounted, TBC, Wall Mounted, Ceiling Mounted
Accessories	Microwave Sensor, Dimming Sensor (0%-100%-25%-10%-0%), Emergency
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 350mmØ
Size - Height	Height: 110mmH
Beam Angle	TBC, Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die-Casting Aluminum

ATTRIBUTE	VALUES
Operating Temperature	Operating Temperature: -30°C to 60°C
Accessories	Microwave Sensor, Dimming Sensor (0%-100%-25%-10%-0%), Emergency

Certification and Compliance

