

## Tahlee Series - 104 - 15W



### Technical Specifications

ATTRIBUTE	VALUES
Wattages	9, 11W, 12W, TBC, 15W
Efficacy	90-100lm/W
Correlated Colour Index (CRI)	>80, >90, >97, TBC
MacAdam Ellipse (SDCM)	<3
IP Rating	20, TBC
Voltage	AC220-240V, 50/60Hz
Light Source & Brand	LED: Citizen COB
Driver	Driver: BOKE, Driver: AIDimming
Size - Diameter	Diameter: 104mmØ
Size - Height	Height: 108mmH
Cut Out Size - Diameter	Cut Out: 95mmØ
Weight	Weight: 0.61kg
Tilt	Tilt: 10-15°
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 38°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics-Glare control	Optics Material: Polycarbonate
Operating Temperature	Operating Temperature: -15°C to 40°C
Trim / Outer Colour	Trim/Outer: White
Reflector / Internal Colour	Reflector/Internal: White, Reflector/Internal: Black, Reflector/Internal: Shiny Silver, Reflector/Internal: Shiny Black, Reflector/Internal: Matt Silver
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K
Mounting Options	TBC, Recessed
Lens Options	Honeycomb, TBC
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

## Product Options

ATTRIBUTE	VALUES
-----------	--------

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 104mmØ
Size - Height	Height: 108mmH
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 38°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -15°C to 40°C

## Certification and Compliance

