

Brighton Series - 180-240W

[AES-03-PL01-G3-180-240W]



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------|-----------------------------|
| Wattages | TBC, 160W, 180W, 200W, 240W |
| Efficacy | 140lm/W |
| Correlated Colour Index (CRI) | >80 |
| IP Rating | 66 |
| IK Rating | 09 |
| Voltage | AC100-277V |
| Light Source & Brand | LED: SMD 3030 |

| ATTRIBUTE | VALUES |
|-------------------------------------|--|
| Driver | Driver: Meanwell |
| Size - Length | Length: 779mmL |
| Size - Width | Width: 328mmW |
| Size - Height | Height: 141mmH |
| Weight | Weight: 8.5kg |
| Mounting Options | TBC, Horizontal Pole Arms, Vertical Pole Arms |
| Beam Angle | TBC, Beam Angle: 150°, Beam Angle: Type II-S - 151° x 81°, Beam Angle: Type II-M - 147° x 72°, Beam Angle: Type III-M - 156° x 71°, Beam Angle: Type IV-M - 100° x 65° |
| Dimming Options | Non-Dimmable, TBC, DALI Dimmable |
| Correlated Colour Temperature (CCT) | CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K |
| Accessories | Microwave Sensor, PIR Sensor, PhotoElectric Cell, 10kV Surge Protection Device, 20kV Surge Protection Device, Short Circuit Cap |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -40°C to+50°C |
| Lifetime | Reported L80 @ 85° >72,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes |

Product Options

| ATTRIBUTE | VALUES |
|-----------------------|--|
| Size - Length | Length: 779mmL |
| Size - Height | Height: 141mmH |
| Beam Angle | TBC, Beam Angle: 150°, Beam Angle: Type II-S - 151° x 81°, Beam Angle: Type II-M - 147° x 72°, Beam Angle: Type III-M - 156° x 71°, Beam Angle: Type IV-M - 100° x 65° |
| Dimming Options | Non-Dimmable, TBC, DALI Dimmable |
| Accessories | Microwave Sensor, PIR Sensor, PhotoElectric Cell, 10kV Surge Protection Device, 20kV Surge Protection Device, Short Circuit Cap |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -40°C to+50°C |

Certification and Compliance

