

Daintree Series - 142



Technical Specifications

ATTRIBUTE	VALUES
Wattages	20W, 30W
Efficacy	100-110lm/W
Correlated Colour Index (CRI)	CRI: >80, CRI: >90, CRI: >97
MacAdam Ellipse (SDCM)	SDCM: <3
IP Rating	IP20
Voltage	AC220-240V, 50/60Hz
Light Source & Brand	LED: Citizen COB
Driver	Driver: BOKE, Driver: AIDimming
Size - Diameter	Diameter: 142mmØ
Size - Height	Height: 118mmH
Cut Out Size - Diameter	Cut Out: 110mmØ
Weight	Weight: 0.78kg
Tilt	Tilt: 15°-20°
Beam Angle	Beam Angle: 24°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics	Optics Material: Polycarbonate
Operating Temperature	Operating Temperature: -15°C to 40°C
Trim / Outer Colour	Trim/Outer: White
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K
Mounting Options	Recessed
Lens Options	Faceted Reflector
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 142mmØ
Size - Height	Height: 118mmH
Beam Angle	Beam Angle: 24°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable

ATTRIBUTE	VALUES
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -15°C to 40°C

Certification and Compliance

