

Daintree Series - 194

[AES-20-C3-194]



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------------|--|
| Wattages | TBC, 50W, 60W |
| Efficacy | 100-110lm/W |
| Correlated Colour Index (CRI) | >80, >90, >97, TBC |
| MacAdam Ellipse (SDCM) | <3 |
| IP Rating | 20, TBC |
| Voltage | AC220-240V, 50/60Hz |
| Light Source & Brand | LED: Citizen COB |
| Driver | Driver: BOKE |
| Size - Diameter | Diameter: 194mmØ |
| Size - Height | Height: 149mmH |
| Cut Out Size - Diameter | Cut Out: 160-170mm Ø |
| Weight | Weight: 1.56kg |
| Tilt | Tilt: 15°-20° |
| Beam Angle | TBC, Beam Angle: 24°, Beam Angle: 40°, Beam Angle: 60° |
| Dimming Options | Non-Dimmable, TBC, DALI Dimmable |
| Material of Housing | Housing Material: Aluminium |
| Material of Optics- Glare control | Optics Material: Polycarbonate |
| Operating Temperature | Operating Temperature: -15°C to 40°C |
| Trim / Outer Colour | Trim/Outer: White |
| Correlated Colour Temperature (CCT) | CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K |
| Mounting Options | TBC, Recessed |
| Lens Options | TBC, Faceted Reflector |
| Lamp Life | Lamp Life: L80 B10 @ 4K, CRI80 |

Product Options

| ATTRIBUTE | VALUES |
|-----------------|--|
| Size - Diameter | Diameter: 194mmØ |
| Size - Height | Height: 149mmH |
| Beam Angle | TBC, Beam Angle: 24°, Beam Angle: 40°, Beam Angle: 60° |

| ATTRIBUTE | VALUES |
|-----------------------|--------------------------------------|
| Dimming Options | Non-Dimmable, TBC, DALI Dimmable |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -15°C to 40°C |

Certification and Compliance

