

Daintree Series - 233

[AES-20-C3-233]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 60W, 80W
Efficacy	100-110lm/W
Correlated Colour Index (CRI)	>80, >90, >97, TBC
MacAdam Ellipse (SDCM)	<3
IP Rating	20, TBC
Voltage	AC220-240V, 50/60Hz
Light Source & Brand	LED: Citizen COB
Driver	Driver: BOKE
Size - Diameter	Diameter: 233mmØ
Size - Height	Height: 149mmH, Height: 169mmH
Cut Out Size - Diameter	Cut Out: 210mmØ
Weight	Weight: 2.8kg, Weight: 2.25kg
Tilt	Tilt: 15°-20°
Beam Angle	TBC, Beam Angle: 24°, Beam Angle: 60°
Dimming Options	Non-Dimmable, TBC, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Optics Material: Polycarbonate
Operating Temperature	Operating Temperature: -15°C to 40°C
Trim / Outer Colour	Trim/Outer: White
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K
Mounting Options	TBC, Recessed
Lens Options	TBC, Faceted Reflector
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 233mmØ
Size - Height	Height: 149mmH, Height: 169mmH
Beam Angle	TBC, Beam Angle: 24°, Beam Angle: 60°

ATTRIBUTE	VALUES
Dimming Options	Non-Dimmable, TBC, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -15°C to 40°C

Certification and Compliance

