

Abbeywood Series - 240-300W



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 240W, 300W
Efficacy	150lm/W
Correlated Colour Index (CRI)	>70, >80, TBC
MacAdam Ellipse (SDCM)	<5
IP Rating	66, TBC
IK Rating	08
Voltage	AC220-240V, 50/60Hz
Light Source & Brand	LED: SMD
Driver	Driver: Done
Size - Length	Length: 495mmL
Size - Width	Width: 419mmW
Size - Height	Height: 75mmH
Weight	Weight: 7.8kg
Vertical Rotation	Vertical Rotation: 45°
Beam Angle	TBC, Beam Angle: 25°, Beam Angle: 60°, Beam Angle: Type I - 26° x 60°, Beam Angle: Type III - 55° x 125°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die-Casting Aluminum Alloy
Material of Optics- Glare control	Optics Material: Polycarbonate
Corrosion Resistance	Corrosion Resistance: C3
Operating Temperature	Operating Temperature: -30°C to +50°C
Trim / Outer Colour	Trim/Outer: Black
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K
Mounting Options	TBC, Pole Mounted, Bracket Mounted
Accessories	42mm Pole Mounting Adaptor, 76mm Pole Mounting Adaptor, 60mm Pole Mounting Adaptor, Clamp Bracket (40mm-150mm pole)
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 495mmL
Size - Height	Height: 75mmH
Beam Angle	TBC, Beam Angle: 25°, Beam Angle: 60°, Beam Angle: Type I - 26° x 60°, Beam Angle: Type III - 55° x 125°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die-Casting Aluminum Alloy
Operating Temperature	Operating Temperature: -30°C to +50°C
Accessories	42mm Pole Mounting Adaptor, 76mm Pole Mounting Adaptor, 60mm Pole Mounting Adaptor, Clamp Bracket (40mm-150mm pole)

Certification and Compliance

