

Haddon Series - 500

[AES-20-E1-500]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 3 x 12W (36W), 3 x 20W (60W), 3 x 30W (90W)
Efficacy	100-110lm/W
Correlated Colour Index (CRI)	>80, >90, >97, TBC
MacAdam Ellipse (SDCM)	<3
IP Rating	20, TBC
Voltage	AC220-240V, 50/60Hz
Light Source & Brand	LED: Citizen COB
Driver	Driver: BOKE, Driver: AIDimming
Size - Length	Length: 500mmL
Size - Width	Width: 185mmW
Size - Height	Height: 165mmH
Cut Out Size - Length	Cut Out: 165mmL, Cut Out: 480mmL
Cut Out Size - Width	Cut Out: 165mmW
Weight	Weight: 3.7kg
Tilt	Tilt: 15°-20°
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 60°
Operating Temperature	Operating Temperature: -15°C to 40°C
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Optics Material: Polycarbonate
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Reflector / Internal Colour	Reflector/Internal: White, Reflector/Internal: Black
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K
Mounting Options	TBC, Recessed
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 500mmL

ATTRIBUTE	VALUES
Size - Height	Height: 165mmH
Cut Out Size - Length	Cut Out: 165mmL, Cut Out: 480mmL
Cut Out Size - Width	Cut Out: 165mmW
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 60°
Operating Temperature	Operating Temperature: -15°C to 40°C
Material of Housing	Housing Material: Aluminium
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable

Certification and Compliance

