

Ikewa Series - 135

[AES-20-C66-135]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 26W, 28W, 30W
Efficacy	100-110lm/W
Correlated Colour Index (CRI)	>80, >90, >97, TBC
MacAdam Ellipse (SDCM)	<3
IP Rating	20, TBC
Voltage	AC220-240V, 50/60Hz
Light Source & Brand	LED: Citizen COB
Driver	Driver: BOKE, Driver: AIDimming

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 135mmØ
Size - Height	Height: 125mmH
Cut Out Size - Diameter	Cut Out: 115-120mm Ø
Weight	Weight: 0.93kg
Tilt	Tilt: 15°
Vertical Rotation	Vertical Rotation: 355°
Horizontal Rotation	Horizontal Rotation: 355°
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Optics Material: Polycarbonate
Operating Temperature	Operating Temperature: -15°C to 40°C
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Reflector / Internal Colour	Reflector/Internal: White, Reflector/Internal: Black
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K
Mounting Options	TBC, Recessed
Lens Options	Honeycomb, TBC
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 135mmØ
Size - Height	Height: 125mmH
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -15°C to 40°C

Certification and Compliance

