

Backwater Series - 100

[AES-15-IP67-100]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	6W, 8W, 10W, TBC
Efficacy	90lm/W
Correlated Colour Index (CRI)	>80, >90, TBC
IP Rating	67, TBC
Voltage	AC220-240V
Light Source & Brand	LED: Cree COB
Driver	Driver: Lifud
Size - Diameter	Diameter: 100mmØ
Size - Height	Height: 75mmH
Cut Out Size - Diameter	Cut Out: 90mmØ
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Silver, Trim/Outer: Gold
Mounting Options	TBC, Recessed
Beam Angle	TBC, Beam Angle: 30°, Beam Angle: 45°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K
Lens Options	TBC, Injection Moulded Lens
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20° to 40°

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 100mmØ
Size - Height	Height: 75mmH
Beam Angle	TBC, Beam Angle: 30°, Beam Angle: 45°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20° to 40°

Certification and Compliance

