

Backwater Series - 140



Technical Specifications

ATTRIBUTE	VALUES
Wattages	10W, 12W, 14W, 16W, 18W, 20W
Efficacy	90lm/W
Correlated Colour Index (CRI)	CRI: >80, CRI: >90
IP Rating	IP67
Voltage	AC220-240V
Light Source & Brand	LED: Cree COB
Driver	Driver: Lifud
Size - Diameter	Diameter: 140mmØ
Size - Height	Height: 90mmH
Cut Out Size - Diameter	Cut Out: 130mmØ
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Silver, Trim/Outer: Gold
Mounting Options	Recessed
Beam Angle	Beam Angle: 30°, Beam Angle: 45°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K
Lens Options	Injection Moulded Lens
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20° to 40°

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 140mmØ
Size - Height	Height: 90mmH
Beam Angle	Beam Angle: 30°, Beam Angle: 45°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20° to 40°

Certification and Compliance

