

# Kagaru 30 Series

[AES-15-D1001A-R5]



## Technical Specifications

| ATTRIBUTE                           | VALUES   |
|-------------------------------------|--|
| Wattages                            | TBC, 20W, 22W, 24W, 26W, 28W, 30W  |
| Efficacy                            | 90lm/W   |
| Correlated Colour Index (CRI)       | >80, >90, TBC  |
| IP Rating                           | 65, TBC  |
| Voltage                             | AC220-240V   |
| Light Source & Brand                | LED: Cree COB  |
| Driver                              | Driver: Lifud  |
| Size - Diameter                     | Diameter: 165mmØ   |
| Size - Height                       | Height: 80mmH  |
| Cut Out Size - Diameter             | Cut Out: 145mmØ  |
| Trim / Outer Colour                 | Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Silver, Trim/Outer: Gold         |
| Mounting Options                    | TBC, Recessed  |
| Beam Angle                          | TBC, Beam Angle: 60°   |
| Dimming Options                     | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable                   |
| Correlated Colour Temperature (CCT) | CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K |
| Lens Options                        | TBC, Tempered Glass Lens   |
| Material of Housing                 | Housing Material: Aluminium, Housing Material: Faceted Reflector                   |
| Operating Temperature               | Operating Temperature: -15°C to 40°C   |

## Product Options

| ATTRIBUTE             | VALUES   |
|-----------------------|--|
| Size - Diameter       | Diameter: 165mmØ   |
| Size - Height         | Height: 80mmH  |
| Beam Angle            | TBC, Beam Angle: 60°   |
| Dimming Options       | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Material of Housing   | Housing Material: Aluminium, Housing Material: Faceted Reflector |
| Operating Temperature | Operating Temperature: -15°C to 40°C                             |

## Certification and Compliance

