

Abbotsbury Series - 150W

[AES-25-HB24-150W]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 150W
Efficacy	190lm/W
Correlated Colour Index (CRI)	>70, >80, TBC
MacAdam Ellipse (SDCM)	<5
IP Rating	65, TBC
IK Rating	08
Voltage	AC100-277V
Light Source & Brand	LED: SMD
Driver	Driver: Lifud
Size - Diameter	Diameter: 280mmØ
Size - Height	Height: 163mmH
Beam Angle	TBC, Beam Angle: 60°, Beam Angle: 90°, Beam Angle: 120°
Dimming Options	Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K
Accessories	Aluminium Reflector, Motion Sensor, Ripple Lens, PC Refractor Attachment, 1.2m Suspension Chain, Surface Mounted Bracket

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 280mmØ
Size - Height	Height: 163mmH
Beam Angle	TBC, Beam Angle: 60°, Beam Angle: 90°, Beam Angle: 120°
Dimming Options	Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable
Accessories	Aluminium Reflector, Motion Sensor, Ripple Lens, PC Refractor Attachment, 1.2m Suspension Chain, Surface Mounted Bracket

Certification and Compliance

