

Alice 10 Series

[AES-15-D1001B-S3]



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------------|------------------------------------------------------------------------------------|
| Wattages | 6W, 8W, 10W, TBC |
| Efficacy | 90lm/W |
| Correlated Colour Index (CRI) | >80, >90, TBC |
| IP Rating | 65, TBC |
| Voltage | AC220-240V |
| Light Source & Brand | LED: Cree COB |
| Driver | Driver: Lifud |
| Size - Length | Length: 110mmL |
| Size - Width | Width: 110mmW |
| Size - Height | Height: 59mmH |
| Cut Out Size - Length | Cut Out: 90mmL |
| Cut Out Size - Width | Mounting Sleeve: 90mmW |
| Trim / Outer Colour | Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Silver, Trim/Outer: Gold |
| Mounting Options | TBC, Recessed |
| Beam Angle | TBC, Beam Angle: 60° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Correlated Colour Temperature (CCT) | CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K |
| Lens Options | TBC, Tempered Glass Lens |
| Material of Housing | Housing Material: Aluminium, Housing Material: Faceted Reflector |
| Operating Temperature | Operating Temperature: -15°C to 40°C |

Product Options

| ATTRIBUTE | VALUES |
|-----------------------|------------------------|
| Size - Length | Length: 110mmL |
| Size - Height | Height: 59mmH |
| Cut Out Size - Length | Cut Out: 90mmL |
| Cut Out Size - Width | Mounting Sleeve: 90mmW |
| Beam Angle | TBC, Beam Angle: 60° |

| ATTRIBUTE | VALUES |
|-----------------------|------------------------------------------------------------------|
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Material of Housing | Housing Material: Aluminium, Housing Material: Faceted Reflector |
| Operating Temperature | Operating Temperature: -15°C to 40°C |

Certification and Compliance

