

# Abbotsbury Series - 200W

[AES-25-HB24-200W]



## Technical Specifications

| ATTRIBUTE                           | VALUES   |
|-------------------------------------|--|
| Wattages                            | TBC, 200W  |
| Efficacy                            | 190lm/W  |
| Correlated Colour Index (CRI)       | >70, >80, TBC  |
| MacAdam Ellipse (SDCM)              | <5   |
| IP Rating                           | 65, TBC  |
| IK Rating                           | 08   |
| Voltage                             | AC100-277V   |
| Light Source & Brand                | LED: SMD   |
| Driver                              | Driver: Lifud  |
| Size - Diameter                     | Diameter: 320mmØ   |
| Size - Height                       | Height: 163mmH   |
| Beam Angle                          | TBC, Beam Angle: 60°, Beam Angle: 90°, Beam Angle: 120°  |
| Dimming Options                     | Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable   |
| Correlated Colour Temperature (CCT) | CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K   |
| Accessories                         | Aluminium Reflector, Motion Sensor, Ripple Lens, PC Refractor Attachment, 1.2m Suspension Chain, Surface Mounted Bracket |

## Product Options

| ATTRIBUTE       | VALUES   |
|-----------------|--|
| Size - Diameter | Diameter: 320mmØ   |
| Size - Height   | Height: 163mmH   |
| Beam Angle      | TBC, Beam Angle: 60°, Beam Angle: 90°, Beam Angle: 120°  |
| Dimming Options | Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable   |
| Accessories     | Aluminium Reflector, Motion Sensor, Ripple Lens, PC Refractor Attachment, 1.2m Suspension Chain, Surface Mounted Bracket |

## Certification and Compliance

