

Caddens 60 Series - R

[AES-15-SD-AC-60]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	3W, 5W, 7W, TBC
Efficacy	90lm/W
Correlated Colour Index (CRI)	>80, >90, >95, TBC
IP Rating	54, TBC
Voltage	AC220-240V
Light Source & Brand	LED: Osram COB
Driver	Driver: Lifud
Shape	Round
Size - Diameter	Diameter: 65mmØ

ATTRIBUTE	VALUES
Size - Height	Height: 59mmH
Cut Out Size - Diameter	Cut Out: 60mmØ
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Silver, Trim/Outer: Charcoal, Trim/Outer: Gold
Mounting Options	TBC, Recessed
Beam Angle	TBC, Beam Angle: 18°, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: Wall Washer
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 65mmØ
Size - Height	Height: 59mmH
Beam Angle	TBC, Beam Angle: 18°, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: Wall Washer
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

Certification and Compliance

