

Galston Series - 115



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------------|--|
| Wattages | 6, 8, 10W, TBC |
| Efficacy | 90lm/W |
| Correlated Colour Index (CRI) | >90, >95, >97, TBC |
| MacAdam Ellipse (SDCM) | <3 |
| IP Rating | 20, TBC |
| IK Rating | 02 |
| Voltage | AC220-240V, 50/60Hz |
| Light Source & Brand | LED: COB |
| Driver | Driver: Lifud, Driver: AIDimming, Driver: CUPower |
| Size - Diameter | Diameter: 115mmØ |
| Size - Height | Height: 64mmH |
| Cut Out Size - Diameter | Cut Out: 100mmØ |
| Beam Angle | TBC, Beam Angle: 50° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Material of Housing | Housing Material: Aluminium |
| Material of Optics- Glare control | Optics Material: Polycarbonate |
| Operating Temperature | Operating Temperature: -15°C to 40°C |
| Trim / Outer Colour | Trim/Outer: White, Trim/Outer: Black |
| Reflector / Internal Colour | Reflector/Internal: Silver |
| Correlated Colour Temperature (CCT) | CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K |
| Mounting Options | TBC, Recessed |
| Lamp Life | Lamp Life: L80 B10 @ 4K, CRI80 |

Product Options

| ATTRIBUTE | VALUES |
|-----------------|--|
| Size - Diameter | Diameter: 115mmØ |
| Size - Height | Height: 64mmH |
| Beam Angle | TBC, Beam Angle: 50° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |

| ATTRIBUTE | VALUES |
|-----------------------|--------------------------------------|
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -15°C to 40°C |

Certification and Compliance

