

Ulong 66 Series

[AES-15-TRS-66]



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------------|------------------------------------------------------------------------------------|
| Wattages | 5W, 7W, 9W, TBC |
| Efficacy | 90lm/W |
| Correlated Colour Index (CRI) | >80, >90, TBC |
| IP Rating | 20, TBC |
| Voltage | AC220-240V |
| Light Source & Brand | LED: Cree COB |
| Size - Diameter | Diameter: 70mmØ |
| Size - Height | Height: 78mmH |
| Cut Out Size - Diameter | Cut Out: 65mmØ |
| Trim / Outer Colour | Trim/Outer: White, Trim/Outer: Silver |
| Mounting Options | TBC, Recessed |
| Beam Angle | TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 60° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Correlated Colour Temperature (CCT) | CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K |
| Lens Options | TBC, Injection Moulded Lens |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -15°C to 40°C |

Product Options

| ATTRIBUTE | VALUES |
|-----------------------|-------------------------------------------------------------------------|
| Size - Diameter | Diameter: 70mmØ |
| Size - Height | Height: 78mmH |
| Beam Angle | TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 60° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -15°C to 40°C |

Certification and Compliance

