

Paechtown Series - 137



Technical Specifications

ATTRIBUTE	VALUES
Wattages	20W, 25W, 30W
Efficacy	120lm/W
Correlated Colour Index (CRI)	CRI: >90, CRI: >95, CRI: >97
MacAdam Ellipse (SDCM)	SDCM: <3
IP Rating	IP20
Voltage	AC220-240V, 50/60Hz
Light Source & Brand	LED: Bridgelux COB
Driver	Driver: Lifud, Driver: AIDimming, Driver: CUPower
Size - Diameter	Diameter: 137mmØ
Size - Height	Height: 101mmH
Cut Out Size - Diameter	Cut Out: 130mmØ
Weight	Weight: 0.4kg
Beam Angle	Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics	Optics Material: Plastic
Operating Temperature	Operating Temperature: -20°C to +40°C
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Reflector / Internal Colour	Reflector/Internal: Silver, Reflector/Internal: Matt White, Reflector/Internal: Peacock Blue, Reflector/Internal: Matt Gold
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 6500K
Mounting Options	Recessed
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 137mmØ
Size - Height	Height: 101mmH
Beam Angle	Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 60°

ATTRIBUTE	VALUES
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

Certification and Compliance

