


# Pagewood Series - Square - 71

[AES-15-510-S-71]



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	3W, 5W, 7W, TBC
Efficacy	100lm/W
Correlated Colour Index (CRI)	>90, >95, >97, TBC
MacAdam Ellipse (SDCM)	<3
IP Rating	20, TBC
IK Rating	01
Voltage	AC220-240V, 50/60Hz
Light Source & Brand	LED: Cree COB
Driver	Driver: Lifud, Driver: AIDimming, Driver: CUPower
Size - Length	Length: 71mmL
Size - Width	Width: 71mmW
Size - Height	Height: 66mmH
Cut Out Size - Length	Cut Out: 65mmL
Cut Out Size - Width	Mounting Sleeve: 65mmW
Tilt	Tilt: 30°
Horizontal Rotation	Horizontal Rotation: 360°
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Optics Material: Polycarbonate
Operating Temperature	Operating Temperature: -20°C to +40°C
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 6500K
Mounting Options	TBC, Recessed
Frame Option	Framed
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

## Product Options

ATTRIBUTE	VALUES
-----------	--------

ATTRIBUTE	VALUES
Size - Length	Length: 71mmL
Size - Height	Height: 66mmH
Cut Out Size - Length	Cut Out: 65mmL
Cut Out Size - Width	Mounting Sleeve: 65mmW
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

## Certification and Compliance

