

Earlwood Duo Series - 15



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------|---|
| Wattages | 2 x 9W (18W), 2 x 11W (22W), 2 x 13W (26W), 2 x 15W (30W) |
| Efficacy | 90lm/W |
| Correlated Colour Index (CRI) | CRI: >80, CRI: >90 |
| IP Rating | IP20 |
| Voltage | AC220-240V |
| Light Source & Brand | LED: Cree COB |
| Size - Length | Length: 210mmL |
| Size - Width | Width: 105mmW |
| Size - Height | Height: 45mmH |
| Cut Out Size - Length | Cut Out: 200mmL |
| Cut Out Size - Width | Mounting Sleeve: 95mmW |
| Trim / Outer Colour | Trim/Outer: White, Trim/Outer: Black |
| Mounting Options | Recessed |

| ATTRIBUTE | VALUES |
|-------------------------------------|--|
| Beam Angle | Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36° |
| Dimming Options | Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable |
| Correlated Colour Temperature (CCT) | CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K |
| Lens Options | Injection Moulded Lens |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -15°C to 40°C |

Product Options

| ATTRIBUTE | VALUES |
|-----------------------|---|
| Size - Length | Length: 210mmL |
| Size - Height | Height: 45mmH |
| Cut Out Size - Length | Cut Out: 200mmL |
| Cut Out Size - Width | Mounting Sleeve: 95mmW |
| Beam Angle | Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36° |
| Dimming Options | Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -15°C to 40°C |

Certification and Compliance

