

Fairymead 75 Series - R



Technical Specifications

ATTRIBUTE	VALUES
-----------	--------

ATTRIBUTE	VALUES
Wattages	8, 10W, 12W, TBC
Efficacy	90lm/W
Correlated Colour Index (CRI)	>80, >90, TBC
IP Rating	20, TBC
Voltage	AC220-240V
Light Source & Brand	LED: Cree COB
Size - Diameter	Diameter: 85mmØ
Size - Height	Height: 63mmH
Cut Out Size - Diameter	Cut Out: 75mmØ
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Mounting Options	TBC, Recessed
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K
Lens Options	TBC, Honeycomb Diffuser
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -15°C to 40°C

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 85mmØ
Size - Height	Height: 63mmH
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -15°C to 40°C

Certification and Compliance

