

Switch Series - 15W-H

[AES-10-X20A-H-15]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	9W, 11W, 13W, TBC, 15W
Efficacy	107lm/W
Correlated Colour Index (CRI)	>80, >97, TBC
IP Rating	20, 44, 65, TBC
Voltage	AC220-240V
Light Source & Brand	LED: Citizen COB
Size - Diameter	Diameter: 50mmØ
Size - Height	Height: 96mmH
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Chrome, Trim/Outer: Custom Colour
Mounting Options	TBC, Recessed

ATTRIBUTE	VALUES
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 55°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5500K, CCT: 6000K, CCT: 6700K
Accessories	Honeycomb Optics, Frosted Centre
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +50°C
Lifetime	Reported L80 @ 55° >55,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 50mmØ
Size - Height	Height: 96mmH
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 55°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Accessories	Honeycomb Optics, Frosted Centre
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +50°C

Certification and Compliance

