

Takone 75 Series



Technical Specifications

ATTRIBUTE	VALUES
Wattages	6W, 8W, 10W
Efficacy	90lm/W
Correlated Colour Index (CRI)	CRI: >80, CRI: >90

03 8761 6734 accounts@ausecotech.com.au <http://ausecotech.com.au> 62 487 717 179

ATTRIBUTE	VALUES
MacAdam Ellipse (SDCM)	SDCM: <3, SDCM: <2
IP Rating	IP20
Voltage	AC220-240V
Light Source & Brand	LED: Citizen COB
Size - Diameter	Diameter: 75mmØ
Size - Height	Height: 90mmH
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Reflector / Internal Colour	Reflector/Internal: Silver, Reflector/Internal: Matt Black, Reflector/Internal: Matt Grey, Reflector/Internal: Shiny Black, Reflector/Internal: Shiny Grey
Mounting Options	Surface Mounted
Beam Angle	Beam Angle: 12°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 55°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K
Lens Options	Honeycomb Diffuser
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 75mmØ
Size - Height	Height: 90mmH
Beam Angle	Beam Angle: 12°, Beam Angle: 24°, Beam Angle: 38°, Beam Angle: 55°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

Certification and Compliance

