

Ultima 75 Duo Series

[AES-15-OKS-14]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 2 x 3W (6W), 2 x 5W (10W), 2 x 7W (14W)
Efficacy	90lm/W
Correlated Colour Index (CRI)	>80, >90, TBC
IP Rating	20, TBC
Voltage	AC220-240V
Light Source & Brand	LED: Cree COB
Size - Length	Length: 145mmL
Size - Width	Width: 75mmW
Size - Height	Height: 70mmH
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Grey
Mounting Options	Surface Mounted, TBC
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 38°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 145mmL
Size - Height	Height: 70mmH
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 38°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

Certification and Compliance

