

Waikiki Series - 20W



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------------|---|
| Wattages | TBC, 14W, 16W, 18W, 20W |
| Efficacy | 90lm/W |
| Correlated Colour Index (CRI) | >80, >90, >95, TBC |
| MacAdam Ellipse (SDCM) | <3, <2 |
| IP Rating | 65, TBC |
| Voltage | AC220-240V |
| Light Source & Brand | LED: Cree COB |
| Driver | Driver: Lifud |
| Size - Diameter | Diameter: 95mmØ |
| Size - Height | Height: 152mmH |
| Trim / Outer Colour | Trim/Outer: White, Trim/Outer: Black |
| Reflector / Internal Colour | Reflector/Internal: White, Reflector/Internal: Black, Reflector/Internal: Silver, Reflector/Internal: Gold, Reflector/Internal: Rose Gold |
| Mounting Options | Surface Mounted, TBC |
| Beam Angle | TBC, Beam Angle: 20°, Beam Angle: 40°, Beam Angle: 60° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Correlated Colour Temperature (CCT) | CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -20°C to +40°C |

Product Options

| ATTRIBUTE | VALUES |
|-----------------------|--|
| Size - Diameter | Diameter: 95mmØ |
| Size - Height | Height: 152mmH |
| Beam Angle | TBC, Beam Angle: 20°, Beam Angle: 40°, Beam Angle: 60° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -20°C to +40°C |

Certification and Compliance

