

Waikiki Series - 30W



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 20W, 22W, 24W, 26W, 28W, 30W
Efficacy	90lm/W
Correlated Colour Index (CRI)	>80, >90, >95, TBC
MacAdam Ellipse (SDCM)	<3, <2
IP Rating	65, TBC
Voltage	AC220-240V
Light Source & Brand	LED: Cree COB
Driver	Driver: Lifud
Size - Diameter	Diameter: 115mmØ
Size - Height	Height: 152mmH
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Reflector / Internal Colour	Reflector/Internal: White, Reflector/Internal: Black, Reflector/Internal: Silver, Reflector/Internal: Gold, Reflector/Internal: Rose Gold
Mounting Options	Surface Mounted, TBC
Beam Angle	TBC, Beam Angle: 20°, Beam Angle: 40°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 115mmØ
Size - Height	Height: 152mmH
Beam Angle	TBC, Beam Angle: 20°, Beam Angle: 40°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

Certification and Compliance

