

## Waikiki Series - 50W



### Technical Specifications

| ATTRIBUTE                           | VALUES  |
|-------------------------------------|---|
| Wattages                            | TBC, 40W, 42W, 44W, 46W, 48W, 50W   |
| Efficacy                            | 90lm/W  |
| Correlated Colour Index (CRI)       | >80, >90, >95, TBC  |
| MacAdam Ellipse (SDCM)              | <3, <2  |
| IP Rating                           | 65, TBC   |
| Voltage                             | AC220-240V  |
| Light Source & Brand                | LED: Cree COB   |
| Driver                              | Driver: Lifud   |
| Size - Diameter                     | Diameter: 170mmØ  |
| Size - Height                       | Height: 182mmH  |
| Trim / Outer Colour                 | Trim/Outer: White, Trim/Outer: Black  |
| Reflector / Internal Colour         | Reflector/Internal: White, Reflector/Internal: Black, Reflector/Internal: Silver, Reflector/Internal: Gold, Reflector/Internal: Rose Gold |
| Mounting Options                    | Surface Mounted, TBC  |
| Beam Angle                          | TBC, Beam Angle: 20°, Beam Angle: 40°, Beam Angle: 60°  |
| Dimming Options                     | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable  |
| Correlated Colour Temperature (CCT) | CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K  |
| Material of Housing                 | Housing Material: Aluminium   |
| Operating Temperature               | Operating Temperature: -20°C to +40°C   |

## Product Options

| ATTRIBUTE             | VALUES   |
|-----------------------|--|
| Size - Diameter       | Diameter: 170mmØ   |
| Size - Height         | Height: 182mmH   |
| Beam Angle            | TBC, Beam Angle: 20°, Beam Angle: 40°, Beam Angle: 60°           |
| Dimming Options       | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Material of Housing   | Housing Material: Aluminium                                      |
| Operating Temperature | Operating Temperature: -20°C to +40°C                            |

## Certification and Compliance

