

# Calderwood 100 Series

[AES-15-30SQ]



## Technical Specifications

| ATTRIBUTE | VALUES                            |
|-----------|-----------------------------------|
| Wattages  | 10W, 12W, TBC, 14W, 16W, 18W, 20W |

03 8761 6734 sales@ausecotech.com.au <http://ausecotech.com.au> 62 487 717 179

| ATTRIBUTE                           | VALUES   |
|-------------------------------------|--|
| Efficacy                            | 90lm/W   |
| Correlated Colour Index (CRI)       | >80, >90, TBC  |
| IP Rating                           | 20, TBC  |
| Voltage                             | AC220-240V   |
| Light Source & Brand                | LED: Cree COB  |
| Size - Length                       | Length: 110mmL   |
| Size - Width                        | Width: 110mmW  |
| Size - Height                       | Height: 120mmH   |
| Trim / Outer Colour                 | Trim/Outer: White, Trim/Outer: Black                                   |
| Mounting Options                    | Surface Mounted, TBC   |
| Beam Angle                          | TBC, Beam Angle: 20°, Beam Angle: 45°                                  |
| Dimming Options                     | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable       |
| Correlated Colour Temperature (CCT) | CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K |
| Lens Options                        | TBC, Clear Glass Lens  |
| Material of Housing                 | Housing Material: Aluminium  |
| Operating Temperature               | Operating Temperature: -20°C to +40°C                                  |

## Product Options

| ATTRIBUTE             | VALUES   |
|-----------------------|--|
| Size - Length         | Length: 110mmL   |
| Size - Height         | Height: 120mmH   |
| Beam Angle            | TBC, Beam Angle: 20°, Beam Angle: 45°                            |
| Dimming Options       | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Material of Housing   | Housing Material: Aluminium                                      |
| Operating Temperature | Operating Temperature: -20°C to +40°C                            |

## Certification and Compliance

