

# Calderwood 100 Series



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	10W, 12W, 14W, 16W, 18W, 20W
Efficacy	90lm/W

ATTRIBUTE	VALUES
Correlated Colour Index (CRI)	CRI: >80, CRI: >90
IP Rating	IP20
Voltage	AC220-240V
Light Source & Brand	LED: Cree COB
Size - Length	Length: 110mmL
Size - Width	Width: 110mmW
Size - Height	Height: 120mmH
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Mounting Options	Surface Mounted
Beam Angle	Beam Angle: 20°, Beam Angle: 45°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K
Lens Options	Clear Glass Lens
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

## Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 110mmL
Size - Height	Height: 120mmH
Beam Angle	Beam Angle: 20°, Beam Angle: 45°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

## Certification and Compliance

