

Queenton Series - 80



Technical Specifications

ATTRIBUTE	VALUES
-----------	--------

ATTRIBUTE	VALUES
Wattages	7W, 15W, 20W, 22W, 24W
Efficacy	80lm/W
Correlated Colour Index (CRI)	CRI: >80, CRI: >90
MacAdam Ellipse (SDCM)	SDCM: <5, SDCM: <3
IP Rating	IP65
Voltage	AC220-240V
Light Source & Brand	LED: Bridgelux COB
Size - Diameter	Diameter: 86mmØ
Size - Height	Height: 140mmH
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Mounting Options	Surface Mounted
Beam Angle	Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 38°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2200K, CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6000K, CCT: 6500K
Material of Optics	Optics Material: PMMA + Anti-UV lens, Optics Material: PMMA + Anti-UV lens with Reflector Cup
Material of Housing	Housing Material: Die-Casting Aluminum
Operating Temperature	Operating Temperature: -20°C to +40°C
Accessories	Honeycomb Optics

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 86mmØ
Size - Height	Height: 140mmH
Beam Angle	Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 36°, Beam Angle: 38°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Die-Casting Aluminum
Operating Temperature	Operating Temperature: -20°C to +40°C
Accessories	Honeycomb Optics

Certification and Compliance

