


Rutherford Series



Technical Specifications

ATTRIBUTE	VALUES
Wattages	10W, 13W, 15W
Efficacy	80lm/W
Correlated Colour Index (CRI)	CRI: >80, CRI: >90

ATTRIBUTE	VALUES
MacAdam Ellipse (SDCM)	SDCM: <5, SDCM: <3
IP Rating	IP65
IK Rating	IK08
Voltage	AC220-240V
Light Source & Brand	LED: Osram SMD, LED: CREE SMD
Size - Length	Length: 120mmL
Size - Width	Width: 120mmW
Size - Height	Height: 1000mmH
Beam Angle	Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -30°C to +50°C
Trim / Outer Colour	Trim/Outer: Silver, Trim/Outer: Grey, Trim/Outer: Brushed Nickel, Trim/Outer: Cream

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 120mmL
Size - Height	Height: 1000mmH
Beam Angle	Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -30°C to +50°C

Certification and Compliance

