

# Cedarton Series

[AES-12-BO20510B]



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	10W, 13W, TBC, 15W
Efficacy	80lm/W
Correlated Colour Index (CRI)	>80, >90, TBC
MacAdam Ellipse (SDCM)	<5, <3
IP Rating	65, TBC
IK Rating	08
Voltage	AC220-240V
Light Source & Brand	LED: Osram SMD, LED: CREE SMD
Size - Diameter	Diameter: 205mmØ
Size - Height	Height: 210mmH
Beam Angle	TBC, Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable

ATTRIBUTE	VALUES
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -30°C to +50°C
Trim / Outer Colour	Trim/Outer: Black, Trim/Outer: Silver, Trim/Outer: Grey, Trim/Outer: Cream

## Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 205mmØ
Size - Height	Height: 210mmH
Beam Angle	TBC, Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -30°C to +50°C

## Certification and Compliance

