

Gaven Series - 500



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 15W, 25W
Efficacy	95lm/W, 100lm/W
Correlated Colour Index (CRI)	>70, >80, TBC
IP Rating	66, TBC
IK Rating	10
Voltage	AC220-240V

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 135mmØ
Size - Height	Height: 500mmH
Beam Angle	TBC, Beam Angle: Type IV - 45° x 112° (t65°), Beam Angle: Type V - 136° x 123° (t34°)
Dimming Options	Non-Dimmable, TBC, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K
Accessories	PIR Sensor, CCT Selectable Switch, Power Selectable Switch, PhotoElectric Cell
Material of Housing	Housing Material: Polycarbonate
Operating Temperature	Operating Temperature: -30°C to +40°C

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 135mmØ
Size - Height	Height: 500mmH
Beam Angle	TBC, Beam Angle: Type IV - 45° x 112° (t65°), Beam Angle: Type V - 136° x 123° (t34°)
Dimming Options	Non-Dimmable, TBC, DALI Dimmable
Accessories	PIR Sensor, CCT Selectable Switch, Power Selectable Switch, PhotoElectric Cell
Material of Housing	Housing Material: Polycarbonate
Operating Temperature	Operating Temperature: -30°C to +40°C

Certification and Compliance

