

Hannaford Series



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------|-----------------|
| Wattages | TBC, 14W, 25W |
| Efficacy | 95lm/W, 110lm/W |
| Correlated Colour Index (CRI) | >70, >80, TBC |
| IP Rating | 66, TBC |
| IK Rating | 09 |
| Voltage | AC220-240V |

| ATTRIBUTE | VALUES |
|-------------------------------------|--|
| Size - Diameter | Diameter: 135mmØ |
| Size - Height | Height: 500mmH, Height: 1000mmH |
| Beam Angle | TBC, Beam Angle: Type V - 30° x 110° (t36°), Beam Angle: Type V - 161° x 141° (t73°), Beam Angle: Type V |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Correlated Colour Temperature (CCT) | CCT: 3000K, CCT: 4000K, CCT: 5000K |
| Accessories | CCT Selectable Switch, Power Selectable Switch |
| Material of Housing | Housing Material: Polycarbonate |
| Operating Temperature | Operating Temperature: -30°C to +45°C |
| Optical Accessories | Milky PC Cover |

Product Options

| ATTRIBUTE | VALUES |
|-----------------------|--|
| Size - Diameter | Diameter: 135mmØ |
| Size - Height | Height: 500mmH, Height: 1000mmH |
| Beam Angle | TBC, Beam Angle: Type V - 30° x 110° (t36°), Beam Angle: Type V - 161° x 141° (t73°), Beam Angle: Type V |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Accessories | CCT Selectable Switch, Power Selectable Switch |
| Material of Housing | Housing Material: Polycarbonate |
| Operating Temperature | Operating Temperature: -30°C to +45°C |

Certification and Compliance

