

Gazette Series

[AES-01-WP01]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 40W, 70W
Efficacy	140lm/W
Correlated Colour Index (CRI)	>70, >80, TBC
IP Rating	66, TBC

ATTRIBUTE	VALUES
IK Rating	10
Voltage	AC220-240V
Light Source & Brand	LED: SMD
Driver	Driver: Daemay
Size - Length	Length: 282mmL
Size - Width	Width: 125mmW
Size - Height	Height: 205mmH
Trim / Outer Colour	Trim/Outer: Black, Trim/Outer: Dark Brown
Mounting Options	TBC, Wall Mounted
Beam Angle	TBC, Beam Angle: Type I - Short, Beam Angle: Type III - 45° x 150° (t55°)
Dimming Options	Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K
Accessories	PhotoElectric Cell, 10kV Surge Protection Device
Material of Housing	Housing Material: Polycarbonate
Operating Temperature	Operating Temperature: -30°C to +55°C

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 282mmL
Size - Height	Height: 205mmH
Beam Angle	TBC, Beam Angle: Type I - Short, Beam Angle: Type III - 45° x 150° (t55°)
Dimming Options	Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable
Accessories	PhotoElectric Cell, 10kV Surge Protection Device
Material of Housing	Housing Material: Polycarbonate
Operating Temperature	Operating Temperature: -30°C to +55°C

Certification and Compliance

