

Jeremy Series - 140 - SMD Lens



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------------|--|
| Wattages | TBC, 40W, 45W, 48W |
| Efficacy | 80lm/W |
| Correlated Colour Index (CRI) | >80, >90, TBC |
| MacAdam Ellipse (SDCM) | <3 |
| IP Rating | 66, TBC |
| IK Rating | 08 |
| Voltage | AC220-240V, 50/60Hz, DC 24V |
| Light Source & Brand | LED: CREE SMD |
| Driver | Driver: Meanwell, Driver: Eaglerise |
| Size - Diameter | Diameter: 138mmØ |
| Size - Height | Height: 240mmH |
| Weight | Weight: 2-3kg |
| Vertical Rotation | Vertical Rotation: 90° |
| Horizontal Rotation | Horizontal Rotation: 355° |
| Beam Angle | TBC, Beam Angle: 5°, Beam Angle: 8°, Beam Angle: 10°, Beam Angle: 12°, Beam Angle: 20°, Beam Angle: 25°, Beam Angle: 30°, Beam Angle: 40°, Beam Angle: 45°, Beam Angle: 60°, Beam Angle: 10° x 22°, Beam Angle: 15° x 55°, Beam Angle: 20° x 60° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Material of Housing | Housing Material: Die-Cast ADC12 Aluminum |
| Material of Optics- Glare control | Optics Material: 4mm Tempered Glass |
| Operating Temperature | Operating Temperature: -20°C to +40°C |
| Trim / Outer Colour | Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Grey |
| Correlated Colour Temperature (CCT) | CCT: 2700K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 5700K, CCT: 6500K |

| ATTRIBUTE | VALUES |
|------------------|---|
| Mounting Options | TBC, Wall Mounted |
| Lens Options | TBC, Honeycomb Louvre |
| Accessories | Safety Rope (20m+ high-altitude suspended wall installation) |
| Lamp Life | Lamp Life: L80 B10 @ 4K, CRI80 |
| Lifetime | Reported L80 @ 85° >90,700 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes |

Product Options

| ATTRIBUTE | VALUES |
|-----------------------|--|
| Size - Diameter | Diameter: 138mmØ |
| Size - Height | Height: 240mmH |
| Beam Angle | TBC, Beam Angle: 5°, Beam Angle: 8°, Beam Angle: 10°, Beam Angle: 12°, Beam Angle: 20°, Beam Angle: 25°, Beam Angle: 30°, Beam Angle: 40°, Beam Angle: 45°, Beam Angle: 60°, Beam Angle: 10° x 22°, Beam Angle: 15° x 55°, Beam Angle: 20° x 60° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Material of Housing | Housing Material: Die-Cast ADC12 Aluminum |
| Operating Temperature | Operating Temperature: -20°C to +40°C |
| Accessories | Safety Rope (20m+ high-altitude suspended wall installation) |

Certification and Compliance

