

Hanson Series - 280



Technical Specifications

ATTRIBUTE	VALUES
Wattages	40W, 70W
Efficacy	145lm/W
Correlated Colour Index (CRI)	CRI: >70
IP Rating	IP66
IK Rating	IK08
Voltage	AC220-240V

ATTRIBUTE	VALUES
Light Source & Brand	LED: SMD
Driver	Driver: Daemay
Size - Length	Length: 282mmL
Size - Width	Width: 125mmW
Size - Height	Height: 205mmH
Trim / Outer Colour	Trim/Outer: Silver, Trim/Outer: Bronze
Mounting Options	Wall Mounted, JunctionBox
Beam Angle	Beam Angle: Type III - 60° x 150° (t50°)
Dimming Options	Non-Dimmable, 1-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 4000K, CCT: 5000K
Accessories	PhotoElectric Cell
Material of Housing	Housing Material: Polycarbonate
Operating Temperature	Operating Temperature: -30°C to +45°C

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 282mmL
Size - Height	Height: 205mmH
Beam Angle	Beam Angle: Type III - 60° x 150° (t50°)
Dimming Options	Non-Dimmable, 1-10V Dimmable, DALI Dimmable
Accessories	PhotoElectric Cell
Material of Housing	Housing Material: Polycarbonate
Operating Temperature	Operating Temperature: -30°C to +45°C

Certification and Compliance

