

# Hanson Series - 280

[AES-01-UWP05-280]



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 40W, 70W
Efficacy	145lm/W
Correlated Colour Index (CRI)	>70, TBC
IP Rating	66, TBC

ATTRIBUTE	VALUES
IK Rating	08
Voltage	AC220-240V
Light Source & Brand	LED: SMD
Driver	Driver: Daemay
Size - Length	Length: 282mmL
Size - Width	Width: 125mmW
Size - Height	Height: 205mmH
Trim / Outer Colour	Trim/Outer: Silver, Trim/Outer: Bronze
Mounting Options	TBC, Wall Mounted, JunctionBox
Beam Angle	TBC, Beam Angle: Type III - 60° x 150° (t50°)
Dimming Options	Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 4000K, CCT: 5000K
Accessories	PhotoElectric Cell
Material of Housing	Housing Material: Polycarbonate
Operating Temperature	Operating Temperature: -30°C to +45°C

## Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 282mmL
Size - Height	Height: 205mmH
Beam Angle	TBC, Beam Angle: Type III - 60° x 150° (t50°)
Dimming Options	Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable
Accessories	PhotoElectric Cell
Material of Housing	Housing Material: Polycarbonate
Operating Temperature	Operating Temperature: -30°C to +45°C

## Certification and Compliance

